

# Kodak T-MAX 400

| Kodak Developer  | Small Tanks / Petites Cuves / Entwicklungsdozen /<br>Små tankar / Tanques Pequeños / Svilupatrice a<br>Spirale / Kleine Tanks |                   |                   |                  | Exposure Index |
|------------------|-------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------|------------------|----------------|
|                  | 18°C                                                                                                                          | 20°C              | 22°C              | 24°C             |                |
| T-Max RS         | —                                                                                                                             | 7                 | 6                 | 5                | 400            |
| T-Max            | —                                                                                                                             | 7                 | 6 <sup>1/2</sup>  | 6                | 400            |
| D-76             | 9                                                                                                                             | 8                 | 6 <sup>1/2</sup>  | 5 <sup>1/2</sup> | 400            |
| D-76 (1+1)       | 14 <sup>1/2</sup>                                                                                                             | 12 <sup>1/2</sup> | 10                | 9                | 400            |
| HC-110 (Dil.B)   | 6 <sup>1/2</sup>                                                                                                              | 6                 | 5                 | 4 <sup>1/2</sup> | 320            |
| Microdol-X       | 12                                                                                                                            | 10 <sup>1/2</sup> | 8 <sup>1/2</sup>  | 7 <sup>1/2</sup> | 200            |
| Microdol-X (1+3) | —                                                                                                                             | —                 | 18 <sup>1/2</sup> | 16               | 320            |

| Push Processing / Traitement Poussé / Empfindlichkeitssteigernde Entwicklung / Pressad framkalling / Procesado Forzado / Trattamento Spinto / Geforceerd Ontwikkelen |        |                  |                   |      |                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------------------|-------------------|------|------------------|
| Kodak Developer                                                                                                                                                      | 20°C   | 24°C             | 20°C              | 24°C | 24°C             |
|                                                                                                                                                                      | EI 800 |                  | EI 1600           |      | EI 3200          |
| T-Max RS                                                                                                                                                             | 7      | 5                | 10                | 7    | 9 <sup>1/2</sup> |
| T-Max                                                                                                                                                                | 7      | 6                | 10                | 8    | 9 <sup>1/2</sup> |
| D-76                                                                                                                                                                 | 8      | 5 <sup>1/2</sup> | 10 <sup>1/2</sup> | 7    | —                |
| HC-110 (Dil B)                                                                                                                                                       | EI 640 |                  | EI 1280           |      |                  |
|                                                                                                                                                                      | 6      | 4 <sup>1/2</sup> | 8 <sup>1/2</sup>  | 6    |                  |