

KODAK T-MAX 100 PROFESSIONAL FILM

KODAK Εμφανιστής	E.I†	C.I‡	Χρόνοι εμφάνισης (σε λεπτά)				
			18°C	20°C	21°C	22°C	24°C
T-Max 1:4	100	0.56	ΔΕ	8	7 ½	7	6 ½
T-Max 1:4	200	0.56	-	8	-	-	6 ½
T-Max 1:4	400	0.56	-	12	-	-	9
T-Max 1:4	800	0.56	-	-	-	-	10 ½
T-Max 1:7	800	0.56	-	-	-	-	10
T-Max 1:9	800	0.56	-	-	-	-	14
T-Max RS	100	0.56	ΔΕ	8	7	7	6
T-Max RS	200	0.56	-	8	-	-	6
T-Max RS	400	0.56	-	12	-	-	9
T-Max RS	800	0.56	-	-	-	-	11 ½
D-76	100	0.56	10 ½	9	8	7	6
D-76	200	0.56	-	9	-	-	6
D-76	400	0.56	-	11	-	-	7 ½
D-76 1:1	100	0.56	14 ½	12	11	10	8 ½
HC-110 (DIL B)	100	0.56	8	7	6 ½	6	5
HC-110 (DIL B)	200	0.56	-	7	-	-	5
HC-110 (DIL B)	400	0.56	-	9 ½	-	-	6 ½
MICRODOL-X	100	0.56	16	13 ½	12	10 ½	8 ½
MICRODOL-X 1:3	100	0.56	ΔΕ	-	20	18 ½	16